





Technical Data
Saphira



Standard Installation:

- Electrical connections: 230V, 1LNPE, 2.3kW, 10A
- Side water tank 5.5 Litres
- Drip tray 1.5 litre with monitoring

Optional Installations:

- Permanent connection to water mains in water tank
- Drainage (holes in counter)
- Coffee grounds chute (holes in counter)
- Coffee bean container expansion

Holes in counter

Coffee grounds chute Ø 90

Drainage +Fresh water connection Ø 50

As for the rest the local regulations are binding!



Franke Coffee Systems

The art of excellent coffeemaking

Standard models

F 2M H D CE1

2 Grinder, Hot water, Steam and Cappuccinatore CE2

Voltage connection

230V, 1LNPE, 2,3kW, 16A, 50 (60) Hz

Dimensions (WxDxH)

420 mm / 505 mm / 503 mm

Water supply

side water tank 5,5lt.

Drain

Residual water tray with monitoring

Brewing Capacity

Espresso	2 Cups / Minute
Coffee	2 Cups / Minute
Hot water	3 dl / Minute
Cappuccino	2 Cups / Minute
Hot water	1 Cup / Minute

Bean container

250 gr./ option 500 gr. lockable

Cake drawer

40 portion of coffee ground

Weight

18 kg

Buttons

19 product keys

Approvals

CE / CB